



ANNEX D: OPTIONAL OUTPUT CONNECTORS FOR PMP180 SERIES

Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUTS	DESCRIPTION	SUGGESTED MATING CONNECTOR
NIL		(1) +V (2) +V (3) -V (4) -V (SHELL) -V & AC GROUND	4-PIN PLUG WITHOUT LOCK, (MOLDING TYPE)	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
B1		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B2		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B3		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B4		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT