



ANNEX B: OPTIONAL OUTPUT CONNECTORS FOR PMP60 SERIES

Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUPS	DESCRIPTION	SUGGESTED MATING CONNECTOR
NIL		<p><b>SINGLE OUTPUT:</b>            (1) -V      (2) -V            (3) +V      (4) -V            (5) +V</p> <p><b>DUAL OUTPUTS:</b>            (1) COM    (2) COM            (3) V1      (4) N.C.            (5) V2</p> <p><b>TRIPLE OUTPUTS:</b>            (1) COM    (2) COM            (3) V1      (4) V3            (5) V2</p>	5 PIN AT 180°DIN MALE CONNECTOR	5 PIN CONTACTS AT 180°DIN RECEPTACLE, SWITCHCRAFT, TYPE: 57GB5F OR EQUIVALENT
B1		<p><b>CENTER: +V</b>  <b>SLEEVE: -V</b></p>	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B2		<p><b>CENTER: +V</b>  <b>SLEEVE: -V</b></p>	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B3		<p><b>CENTER: -V</b>  <b>SLEEVE: +V</b></p>	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B4		<p><b>CENTER: -V</b>  <b>SLEEVE: +V</b></p>	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
HB		<p>(1) -V      (2) +V            (3) -V      (4) +V</p>	4-PIN PLUG WITH LOCK, KYCON P/N KPPX-4P OR EQUIVALENT	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT