


















Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUTS	DESCRIPTION	SUGGESTED MATING CONNECTOR
NIL		(1) -V (2) +V (3) -V (4) +V EXCEPT PMP90-10,10-1,12,12-1 PMP120-12,13 PMP150-12,13,13-2	4-PIN PLUG WITH LOCK, KYCON P/N KPPX-4P OR EQUIVALENT	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
NIL		(1) -V (2) +V (3) -V (4) +V PMP90-10,10-1,12,12-1 PMP120-12,13 PMP150-12,13,13-2	4-PIN PLUG WITHOUT LOCK, (MOLDING TYPE)	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
B1		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B2		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK & GROOVE TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B3		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B4		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR (FORK TYPE)	
B5		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR (FORK & GROOVE TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B6		CENTER: +V SLEEVE: -V	EIAJ-05 PLUG	Lumberg 1613 11 OR Lumberg 1614 05 OR EQUIVALENT

Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUTS	DESCRIPTION	SUGGESTED MATING CONNECTOR
B7		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B8		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK & GROOVE TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B10		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B14		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	
B16		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (LOCKING FEATURE)	
HF		(1) +V (2) -V (3) N.C.	3-PIN PLUG WITH LOCK, KYCON P/N KPPX-3P OR EQUIVALENT	3-PIN SOCKEY, KYCON P/N KPJX-3S-S OR EQUIVALENT
HI		(1) +V (2) +V (3) -V (4) -V	4-PIN PLUG WITH LOCK, KYCON P/N KPPX-4P OR EQUIVALENT	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
HJ		(1) -V (2) +V (3) -V (4) +V	4-PIN PLUG WITHOUT LOCK, (MOLDING TYPE)	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
Q1		(1) -V (2) -V (3) +V (4) -V (5) +V	5 PIN AT 180°DIN MALE CONNECTOR	5 PIN CONTACTS AT 180°DIN RECEPTACLE, SWITCHCRAFT, TYPE: 57GB5F OR EQUIVALENT