



ANNEX E: OPTIONAL OUTPUT CONNECTORS FOR PUP120 SERIES

Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUTS	DESCRIPTION	SUGGESTED MATING CONNECTOR
NIL		(1) -V (2) +V (3) -V (4) +V (SHELL) -V & AC GROUND	4-PIN PLUG WITHOUT LOCK, (MOLDING TYPE)	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
B1		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B2		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B3		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B4		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B7		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR (FORK & GROOVE TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
D1		(1) -V (2) +V (3) +V (4) +V (5) +V (6) -V (7) -V (8) -V (9) -V	D-SUBMINIATURE 9 PIN RECEPTACLE	D-SUBMINIATURE 9 PIN PLUG. AMP, TYPE: 205865 OR EQUIVALENT
HI		(1) +V (2) +V (3) -V (4) -V	4-PIN PLUG WITH LOCK, KYCON P/N KPPX-4P OR EQUIVALENT	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
Q1		(1) -V (2) -V (3) +V (4) -V (5) +V (6) -V (7) +V (8) +V	8 PIN AT 270° DIN MALE CONNECTOR	8 PIN CONTACTS AT 270° DIN RECEPTACLE, SWITCHCRAFT, TYPE: 62GB8F OR EQUIVALENT