



ANNEX F: OPTIONAL OUTPUT CONNECTORS FOR PUP150N SERIES

Unit: mm

SUFFIX	PROFILE & DIMENSIONS	PINOUTS	DESCRIPTION	SUGGESTED MATING CONNECTOR
NIL		(1) +V (2) +V (3) -V (4) -V (SHELL) -V & AC GROUND	4-PIN PLUG WITHOUT LOCK, (MOLDING TYPE)	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
B1		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B2		CENTER: +V SLEEVE: -V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B3		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA722 OR EQUIVALENT
B4		CENTER: -V SLEEVE: +V	BARREL FEMALE CONNECTOR (FORK TYPE)	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
B8		CENTER: +V SLEEVE: -V	BARREL RIGHT ANGLE FEMALE CONNECTOR	SWITCHCRAFT, TYPE: RA712 OR EQUIVALENT
H1		(1) +V (2) -V (3) +V (4) -V	4-PIN PLUG WITH LOCK, KYCON P/N KPPX-4P OR EQUIVALENT	4-PIN SOCKET, KYCON P/N KPJX-4S-S OR EQUIVALENT
K3		(1) -V (2) -V (3) +V (4) -V (5) +V	5 PIN AT 180° DIN MALE WITH 30° LOCK RING CONNECTOR	SWITCHCRAFT, TYPE: 57HB5F OR EQUIVALENT
Q1		(1) -V (2) -V (3) +V (4) -V (5) +V (6) -V (7) +V (8) +V	8 PIN AT 270° DIN MALE CONNECTOR	8 PIN CONTACTS AT 270° DIN RECEPTACLE, SWITCHCRAFT, TYPE: 62GB8F OR EQUIVALENT